



MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022
Issue date: 10/15/2025 Revision date: 10/15/2025 Version: 1.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : MaxPatch Lightweight Color Changing Spackle

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Recommended use : Patch walls and ceilings and fill holes

1.4. Supplier's details

Manufacturer

DPWagner, LLC
4795 Innovative Way
Suite 100
Powder Springs, GA, 30127
USA
T 630-550 1510
www.dpwagner.com

1.5. Emergency phone number

Emergency number : 678-384-3054

SECTION 2 Hazard identification

2.1. Classification of the substance or mixture

GHS classification

Skin corrosion/irritation, Category 2
Serious eye damage/eye irritation, Category 2A
Carcinogenicity, Category 1B

2.2. Label elements

GHS labelling

Hazard pictograms (GHS) :



Signal word (GHS) :

Danger

Hazard statements (GHS) :

Causes skin irritation

Causes serious eye irritation

May cause cancer.

Precautionary statements (GHS) :

If medical advice is needed, have product container or label at hand.

Keep out of reach of children.

Read label before use.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Wash hands, forearms and face thoroughly after handling.

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Wear protective gloves, protective clothing, eye protection, face protection.
If exposed or concerned: Get medical advice/attention.
If on skin: Wash with plenty of water.
Take off contaminated clothing and wash it before reuse.
If skin irritation occurs: Get medical advice or attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice or attention.
Store locked up.
Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

Not applicable

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Glass, oxide, chemicals	Glass, oxide, chemicals Glass, oxide / Glass / Sodium calcium polyphosphate / Glass powder / Calcium sodium polyphosphate / Sodium calcium polyphosphate silicate / Sodium zinc potassium polyphosphate / Glass flake / Calcium aluminum borosilicate / Glass dust / GLASS / Fiberglass / CALCIUM ALUMINUM BOROSILICATE	CAS-No.: 65997-17-3	10 – 30

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Name	Chemical name / Synonyms	Product identifier	Conc. (% w/w)
Oxirane, methyl-, polymer with oxirane, monobutyl ether	Oxirane, methyl-, polymer with oxirane, monobutyl ether Ethylene oxide-propylene oxide copolymer monobutyl ether / Methyloxirane polymer with oxirane, monobutyl ether / n- Butoxypoly(oxyethylene)-poly(oxypropylene)glycol / Poly(ethylene propylene)glycol monobutyl ether / Polyoxyethylene(45)polyoxypropylene(33)monobutyl ether / PPG-10-BUTETH-9 / PPG-2-buteth-3 / Oxirane, 2-methyl-, polymer with oxirane, monobutyl ether / .alpha.-Butyl-omega.-hydroxypoly(oxyethylene) poly(oxypropylene) / Polymer, oxirane, methyl with oxirane, monobutyl ether / PPG-19-buteth-19 / PPG-17-buteth-17 / PPG-15-buteth-20 / PPG-12-buteth-16 / PPG-12-BUTETH-12 / PPG-12-BUTETH-16 / PPG-15-BUTETH-20 / PPG-2-buteth-1 / PPG-12-buteth-12 / PPG-10-buteth-9 / PPG-24-BUTETH-27 / PPG-28 buteth-35 / Polyoxyethylene polyoxypropylene butyl ether / Oxirane, methyl, polymer and oxibane, butyl ether / PPG-36-BUTETH-36 / PPG-38-BUTETH-37 / PPG-3-BUTETH-5 / PPG-4-BUTETH-4 / PPG-5-BUTETH-5 / PPG-5-BUTETH-7 / PPG-7-BUTETH-10 / PPG-7-BUTETH-4 / PPG-9-BUTETH-12 / Ethoxylated or propoxylated butanol / PPG-buteth / Monobutyl ether of polymer of: 2-methyloxirane; oxirane / PPG-9-buteth-12 / PPG-7-buteth-4 / PPG-7-buteth-10 / PPG-5-buteth-7 / PPG-5-buteth-5 / PPG-4-buteth-4 / PPG-3-buteth-5 / PPG-38-buteth-37 / PPG-36-buteth-36 / PPG-33-buteth-45 / PPG-30-buteth-30 / PPG-2-buteth-2 / PPG-28-buteth-35 / PPG-24-buteth-27 / PPG-20-buteth-30 / PPG-19-BUTETH-19 / PPG-20-BUTETH-30 / PPG-28-BUTETH-35 / PPG-2-BUTETH-1 / PPG-2-BUTETH-2 / PPG-2-BUTETH-3 / PPG-30-BUTETH-30 / PPG-33-BUTETH-45 / PPG-17-BUTETH-17	CAS-No.: 9038-95-3	1 - 5
Potassium hydroxide	Potassium hydroxide Caustic potash / Potassium hydroxide (K(OH)) / POTASSIUM HYDROXIDE	CAS-No.: 1310-58-3	0.1 - 1

*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

SECTION 4 First-aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Get medical advice/attention if you feel unwell.
First-aid measures after skin contact	: IF ON SKIN: Wash with plenty of water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice/attention.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms/effects, acute and delayed

Symptoms/effects after inhalation	: May cause irritation to the respiratory tract.
Symptoms/effects after skin contact	: Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact	: Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion	: May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms	: May cause cancer.

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment : Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media : Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard : Products of combustion may include, and are not limited to: oxides of carbon. Irritating vapours.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting : Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

For non-emergency personnel

No additional information available

For emergency responders

Environmental precautions : Prevent entry to sewers and public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Absorb and/or contain spill with inert material (sand, vermiculite or other appropriate material), then place in suitable container. Do not flush into surface water or sewer system. Wear recommended personal protective equipment.
Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. Provide ventilation.

For further information refer to section 8: "Exposure controls/personal protection"

SECTION 7 Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Do not breathe gas, fumes, vapour or spray.
Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

7.2. Conditions for safe storage, including incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a dry, cool and well-ventilated place. Store locked up.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

Potassium hydroxide (1310-58-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® C	2 mg/m ³
USA - NIOSH - Occupational Exposure Limits	
NIOSH REL C	2 mg/m ³
Glass, oxide, chemicals (65997-17-3)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® TWA	1 fibers/cm ³ (respirable fibers: length >5 µm, aspect ratio ≥3:1, as determined by the membrane filter method at 400-450X magnification [4-mm objective], using phase-contrast illumination (Synthetic vitreous fibers) 5 mg/m ³ (inhalable particulate matter (Synthetic vitreous fibers)

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Hand protection:
Wear suitable gloves resistant to chemical penetration. Consult glove manufacturer's product information on material suitability and material thickness.
Eye protection:
Wear eye/face protection
Skin and body protection:
Wear suitable protective clothing
Respiratory protection:
In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. SDSs cannot provide detailed and complete respiratory protection guidelines. Selection of respiratory protection must be done by a qualified person who has assessed the work environment.

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state : Liquid

Colour : No data available

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Odour	: No data available
Odour threshold	: No data available
pH	: < 10.5
Melting point	: No data available
Freezing point	: No data available
Boiling point	: > 100 °C
Flash point	: > 100 °C
Flammability (solid, gas)	: Not flammable.
Vapour pressure	: No data available
Relative vapour density at 20°C/ 68 °F	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 1000 mm²/s
Explosive limits	: No data available
Particle characteristics	: No data available

Potassium hydroxide	
Boiling point	1320 °C
Vapour pressure	2.6664 – 3.9997 hPa (at 15.6 °C)
Particle characteristics	No data available

Glass, oxide, chemicals	
Boiling point	> 1000 °C (at 1013 hPa (with decomposition))
Particle characteristics	No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Incompatible materials.

10.5. Incompatible materials

Strong oxidizers. Strong acids. Strong bases.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Irritating vapours

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Not classified.

Oxirane, methyl-, polymer with oxirane, monobutyl ether (9038-95-3)

LD50 oral rat	5 g/kg (Source: NLM_CIP)
LD50 dermal rabbit	14100 µl/kg (Source: NLM_CIP)
LC50 inhalation rat	147 mg/m ³ (Exposure time: 4 h Source: NLM_CIP)

Potassium hydroxide (1310-58-3)

LD50 oral rat	284 mg/kg (Source: JAPAN_GHS)
LD50 oral	284 mg/kg

Glass, oxide, chemicals (65997-17-3)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
---------------	---

Skin corrosion/irritation : Causes skin irritation.
pH: < 10.5

Potassium hydroxide (1310-58-3)

pH	13 (conc: 1 % (solution))
----	---------------------------

Serious eye damage/irritation : Causes serious eye irritation.
pH: < 10.5

Potassium hydroxide (1310-58-3)

pH	13 (conc: 1 % (solution))
----	---------------------------

Respiratory or skin sensitisation : Not classified.
Germ cell mutagenicity : Not classified.
Carcinogenicity : May cause cancer.
Reproductive toxicity : Not classified.
STOT-single exposure : Not classified.
STOT-repeated exposure : Not classified.
Aspiration hazard : Not classified.

MaxPatch Lightweight Color Changing Spackle

Viscosity, kinematic	> 1000 mm ² /s
----------------------	---------------------------

Symptoms/effects after inhalation : May cause irritation to the respiratory tract.
Symptoms/effects after skin contact : Causes skin irritation. Symptoms may include redness, drying, defatting and cracking of the skin.
Symptoms/effects after eye contact : Causes serious eye irritation. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva.
Symptoms/effects after ingestion : May be harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Chronic symptoms : May cause cancer.
Other information : Likely routes of exposure: ingestion, inhalation, skin and eye.

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology – general : May cause long-term adverse effects in the aquatic environment.
Hazardous to the aquatic environment, short-term (acute) : Not classified.
Hazardous to the aquatic environment, long-term (chronic) : Not classified.

12.2. Persistence and degradability

MaxPatch Lightweight Color Changing Spackle	
Persistence and degradability	Not established.
Oxirane, methyl-, polymer with oxirane, monobutyl ether (9038-95-3)	
Persistence and degradability	Rapidly degradable
Potassium hydroxide (1310-58-3)	
Persistence and degradability	Rapidly degradable
Glass, oxide, chemicals (65997-17-3)	
Persistence and degradability	Rapidly degradable

12.3. Bioaccumulative potential

MaxPatch Lightweight Color Changing Spackle	
Bioaccumulative potential	Not established.
Potassium hydroxide (1310-58-3)	
Partition coefficient n-octanol/water	0.65

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

Ozone : Not classified.
Fluorinated greenhouse gases : No
Other information : No other effects known.

SECTION 13 Disposal considerations

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

SECTION 14 Transport information

In accordance with DOT / TDG

14.1. UN Number

UN-No. (DOT) : Not regulated
UN-No. (TDG) : Not regulated

MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated
Proper Shipping Name (TDG) : Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated
Packing group (TDG) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

All components of this product are listed, or excluded from listing, on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory.

All components of this product are listed, or excluded from listing, on the Canadian DSL (Domestic Substances List) and NDSL (Non-Domestic Substances List) inventories .

15.2. International regulations

No additional information available

15.3. State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16 Other Information

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

Revision date : 10/15/2025
Issue date : 10/15/2025
Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



MaxPatch Lightweight Color Changing Spackle

Safety Data Sheet

According to the Hazard Communication Standard (CFR29 1910.1200) HazCom 2024 and the Hazardous Products Regulations (HPR) WHMIS 2022

SDS HazCom 2024 - WHMIS 2022 (Nexreg) 2025

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.